

AN IMPROVEMENT OF FLOW FRONT COMPUTATION THROUGH BÉZIER SHAPE DEFORMATION GUARANTEEING MASS CONSERVATION LAW

L. Hilario^{1*}, N. Montés¹, A. Falcó¹, F. Sánchez¹

¹ Universidad CEU Cardenal Herrera. C/ San Bartolomé 55, 46115, Alfara del Patriarca, Valencia (Spain) URL: www.uch.ceu.es. e-mail: luciah@uch.ceu.es; afalco@uch.ceu.es; nimonsan@uch.ceu.es; sanchezf@uch.ceu.es

ABSTRACT: This paper aims to define the flow front as a continuous curve, in particular a Bézier curve, to reduce the inaccuracies generated by classical Finite Elements (FEM) in the flow front definition. The flow front is used in LCM processes for optimization algorithms, on-line control systems, PPI index and in general for whatever design and correction task. In these algorithms it is commonly used FEM simulation where the flow front is represented as a set of discrete points. This fact introduces an inaccuracy with the real flow front, because is continuous. In addition, the shape of the flow front obtained by FEM simulation differs in a great manner from the smooth shape of the real flow front. This concept was solved in our previous research, [7], where, using a mathematical technique, a Bézier curve is deformed and moved using velocity vectors. This technique is called Bézier Shape Deformation. This work improved the flow front representation but also introduced inaccuracies. In particular, the area enclosed between two Bézier curves, the flow front in different time instants, do not corresponds to the resins amount introduced in this range of time. To solve it, in the present research it is guaranteed the mass conservation law. Hence, it is introduced the required enclosed area in the mathematical technique to guarantee that not only velocity vectors has an influence in the Bézier curve deformation.

KEYWORDS: FEM, NEM, RTM, LCM, flow front, Bézier curves, numerical simulation.

1 INTRODUCTION.

The Liquid Composite Molding is the process most used in the production of aeronautic, naval industry, etc. This kind of process uses a mould to manufacture some pieces. After closing the mould is impregnated the preform (a special fiber) by injecting resin. The geometric line between the dry and wet area of the preform is defined as the flow front. It is a common tool to take decisions on-line during the filling of the mould. Usually numerical tools are used to simulate the flow front like Finite Elements Methods. This method introduces inaccuracies because the flow front is represented as a set of discrete points. The shape of the flow front obtained by FEM simulation differs in a great manner from the smooth shape of the real flow front. Actually the flow front is a continuous curve. In general, the relevance of a proper representation of the domain was analyzed in other works like [1],[2],[3]. The idea is represent it as a continuous curve. The parametric curves are widely used for geometry description in CAGD (Computer Aided Graphic Design) because its mathematical properties are interesting. This fact has induced new numerical techniques to obtain a better representation of the computational domain with parametric curves, for examples, Bézier, B-Splines, NURBS, etc. In [4] introduced

isogeometric analysis based on NURBS. The entire domain is defined as a NURBS surface where the simulation is computed. It produces an accurate representation of the flow front but with an unacceptable computational cost. To reduce it, in [5] is combined NURBS-Enhance Finite Element Method (NEFEM) with Discontinuous Galerkin Formulation, FEM. Only the mould contour is defined as a NURBS curve and inside the domain reducing the computational costs. This investigation improves the FE simulation results in the contour but not in the flow front because it is defined as a set of points like in FEM. In [6], the mesh of the domain is obtained by Bézier triangles. Although these works improve the FEM techniques, are not focused in the proper flow front representation. In this sense, a flow front must be a continuous curve that must be moved by velocity vectors obtained in the FEM simulation using Darcy's Law to maintain the computational cost efficiency. This concept was developed in our previous research [7], where a Bézier curve was moved and deformed by velocity vectors.

*Corresponding author: postal address, phone, email address

2 PREVIOUS WORK: BÉZIER SHAPE DEFORMATION. DEFINITIONS AND PROPERTIES.

Definition 1 A Bézier curve of degree n can be represented as:

$$\alpha(t) = \sum_{i=0}^n P_i B_{i,n}(t), t \in [0, 1] \quad (1)$$

where P_i are control points such that $P(0) = P_0$ and $P(1) = P_n$, $B_{i,n}(t)$ is a Bernstein polynomial given by:

$$B_{i,n}(t) = \frac{n!}{i!(n-i)!} (1-t)^{n-i} t^i, i \in 0, 1, \dots, n \quad (2)$$

Bézier curves have useful properties for represent a curve with a physical sense, in particular, an important properties is how to modify its shape. The way to get it, is modify the control points. With this properties it is defined the following operator:

Definition 2

$$S_\varepsilon(\alpha(t)) = \sum_{i=0}^n (P_i + \varepsilon_i) B_{i,n}(t), t \in [0, 1] \quad (3)$$

This definition represent the Bézier curve modify. This modification is made through velocity vectors. These velocity vectors are obtained by Finite Element Methods, joining the start point S and the final point T (Target Point). Another interesting properties is the easily way of concatenate two Bézier curve. Is necessary concatenate two or more Bézier curves to compute the real flow front using Bézier curve of low order. The aim of Bézier Shape Deformation (BSD) is to compute the vector ε , it can be obtained through a constrained optimization method based on Lagrange Multipliers. The idea is to minimize the energy used by the curve from $\alpha(t)$ to $S_\varepsilon(\alpha(t))$, that is,

$$\begin{aligned} & \min \|\mathbf{S}_\varepsilon(\alpha(t)) - \alpha(t)\| \\ & = \int_0^1 (\alpha(t) - \mathbf{S}_\varepsilon(\alpha(t)))^2 dt \\ & = \int_0^1 \left(\sum_{i=0}^n \varepsilon_i B_{i,n}(t) \right)^2 dt \end{aligned} \quad (4)$$

To solve this problem, it is proposed the concatenation of multiple Bézier curves, k , of low order (second order, because the Bézier curve must be injective to avoid the loops). Then, the function to minimize is translated as:

$$\sum_{j=1}^k \int_0^1 \left(\sum_{i=0}^n \varepsilon_i^{(j)} B_{i,n}(t) \right)^2 dt \quad (5)$$

To maintain the derivative property of the curve is imposed to the constrained optimization method the derivative restrictions in the start and end point of the resulting concatenated curve,

$$\alpha'_1(0) - \mathbf{S}'_\varepsilon(\alpha_1(0)) = 0; \alpha'_k(1) - \mathbf{S}'_\varepsilon(\alpha_k(1)) = 0 \quad (6)$$

And in the joined points of the concatenated curves,

$$\mathbf{S}_\varepsilon(\alpha_1(1) - \mathbf{S}_\varepsilon(\alpha_2(0)) = 0 \quad (7)$$

$$\mathbf{S}'_\varepsilon(\alpha_1(1) - \mathbf{S}'_\varepsilon(\alpha_2(0)) = 0 \quad (8)$$

...

$$\mathbf{S}_\varepsilon(\alpha_{k-2}(1) - \mathbf{S}_\varepsilon(\alpha_{k-1}(0)) = 0 \quad (9)$$

$$\mathbf{S}'_\varepsilon(\alpha_{k-2}(1) - \mathbf{S}'_\varepsilon(\alpha_{k-1}(0)) = 0 \quad (10)$$

The Lagrange function can be defined as: $L(\varepsilon_i, \lambda)$

$$\begin{aligned} & = \sum_{l=1}^k \left(\int_0^1 \left(\sum_{i=0}^{n_l} \varepsilon_i^{(l)} B_{i,n_l}(t) \right)^2 dt + \right. \\ & + \sum_{j=1}^{r_l} \lambda_j^{r_l} [T_j^{(l)} - \mathbf{S}_\varepsilon(\alpha_l(t_j))] + \\ & + \lambda^{(2l-2)-1} [\mathbf{S}_\varepsilon(\alpha_{l-1}(1)) - \mathbf{S}_\varepsilon(\alpha_l(0))] \\ & + \lambda^{(2l-2)} [\mathbf{S}'_\varepsilon(\alpha_{l-1}(1)) - \mathbf{S}'_\varepsilon(\alpha_l(0))] \\ & + \lambda_s [\alpha'_1(0) - \mathbf{S}'_\varepsilon(\alpha_1(0))] \\ & \left. + \lambda_{s+1} [\alpha'_k(1) - \mathbf{S}'_\varepsilon(\alpha_k(1))] \right) \end{aligned} \quad (11)$$

Making zero $\frac{\partial L}{\partial \varepsilon}$ and $\frac{\partial L}{\partial \lambda}$ a linear system equations is obtained like $AX = b$, where A is a square matrix, its dimension depends on the order of the matrix. The vector X is the solution and with it the Bézier curve is modified.

3 OBJETIVE AND OUTLINE

The "Bézier Shape Deformation" improved the flow front representation but also introduced inaccuracies. In particular, the area enclosed between two Bézier curves in different time instants do not corresponds to the resin's amount introduced in this range of time. To solve it, in the present research it is guaranteed the mass conservation law. Hence, it is introduced the required enclosed area in the mathematical technique to guarantee that not only velocity vectors has an influence in the Bézier curve deformation. At the end of the paper some examples are shown.

The mathematical technique to develop this tool is the same like in the "Bézier Shape Deformation", a constrained optimization method based on Lagrange multipliers. Only a new constraint is added that guarantees an equality between the area and the resin's amount injected.

4 THEOREM OF GREEN-RIEMANN

Theorem 1 Let $\beta : [a, b] \longrightarrow \mathbb{R}^n$ Jordan's curve piecewise smooth. Let D a convex set bounded by β . β is positively oriented. Let $F = (M, N)$ vector field, $F : A \subset \mathbb{R}^2 \longrightarrow \mathbb{R}^2$, $F \in C^1(A)$ such that $D \subset A$. Then,

$$\int_\beta M dx + N dy = \int \int_D \left(\frac{\partial N}{\partial x} - \frac{\partial M}{\partial y} \right) dA \quad (12)$$

Corollary 2 A consequence of Green-Riemann Theorem is used to compute the area of D as:

$$\text{area}(D) = \int \int_D dA = \int_\beta -y dx \quad (13)$$




Figure 1: Area between two Bézier curves

This result, 2, is used to compute the area enclosed two Bézier curves. In our paper, it is used to compute the area between two flow front's representation in different time instants. This value is compared with the resin's volume injected in this time instant. See Figure 1.

Definition 3 Let $F : A \subset \mathbb{R}^n \rightarrow \mathbb{R}^n$ a continuous vector field and let $\gamma : [a, b] \rightarrow \mathbb{R}^n$ piecewise smooth curve. The line integral along γ is defined as follow:

$$\int_{\gamma} F = \int_a^b F(\gamma) \cdot \gamma'(t) dt \quad (14)$$

5 BÉZIER SHAPE DEFORMATION WITH A PHYSICAL LAW

To develop this new technique a new constraint is added in the Lagrangian function, see 11. The new Lagrangian function will be:

$$\overline{L(\varepsilon, \lambda)} = L(\varepsilon, \lambda) + \lambda(\text{area} - \text{amount}) \quad (15)$$

The area's computation is done with the corollary, see ref:area. With this mathematical result is possible to calculate the area with the boundary's parametrization. In this case, see Figure

reffig:area, the parametrization is known because the flow front is a Bézier curve and the contour of the mold in this previous research is considered as a straight line. In figure reffig:area there are four curves, β_1 , β_2 , β_3 and β_4 . The first and the third one are a concatenated Bézier curves, its parametrization is defined in

refeq:Bezier. The second and the fourth one are segments. The parametrization of these segments are defined as follows:

$$\beta_2 = (x_2(t), y_2(t)) = \mathbf{R}_2 + t\overrightarrow{\mathbf{R}_2\mathbf{R}_3} = \mathbf{R}_2 + t(\mathbf{R}_3 - \mathbf{R}_2) \quad (16)$$

$$t \in [0, 1]$$

$$\beta_4 = (x_4(t), y_4(t)) = \mathbf{R}_4 + t\overrightarrow{\mathbf{R}_4\mathbf{R}_1} = \mathbf{R}_4 + t(\mathbf{R}_1 - \mathbf{R}_4) \quad (17)$$

$$t \in [0, 1]$$

Applying the definition 3 the area of this zone is compute as: (considering $\beta(t) = (x(t), y(t))$)

$$\text{area}(D) = \int_{\beta} -y dx = \int_0^1 F(\beta(t)) \cdot \beta'(t) dt = \quad (18)$$

$$= \sum_{i=1}^4 \int_{\beta_i} -y dx = \sum_{i=1}^4 \int_0^1 -y_i(t) \cdot x'_i(t) dt$$

The result of this area is a function with the control points \mathbf{P}_i of the Bézier curves and another function with the perturbation vector ε_i . Making zero $\frac{\partial L}{\partial \varepsilon}$ and $\frac{\partial L}{\partial \lambda}$ is obtained a no linear system, this is the difference between this method and the Bézier Shape Deformation. The system is $F(X) = 0$ and the solution is $\mathbf{X} = [\varepsilon_i, \lambda]$. The solution is a better representation of the flow front.

6 EXAMPLES

7 CONCLUSIONS

ACKNOWLEDGEMENT

This research work is financially supported by Project DPI2007-66723-C02-02 from the Spanish Government and project PRUCH39/09 of the University CEU Cardinal Herrera.

REFERENCES

- [1] B.Cockburn. Discontinuous Galerkin methods for Computational Fluid Dynamics, vol.3 (Fluids) Encyclopedia of computational mechanics, ch 4. John Wiley & Sons, 2004.
- [2] F.Bassi, S.Rebay. High order accurate discontinuous finite element solution of the 2D Euler equations. Int. Journal Comput. Phys., vol 138, no 2, pp 251-285, 1997.
- [3] D. Xue, L.Demkowicz. Control of geometry induced error in hp finite element (FE) simulations. I. Evaluation of FE error for curvilinear geometries. Int. J. Numer. Anal. Model., vol.2, no 3, pp 283-300, 2005.
- [4] T.J.R. Hughes, J.A. Cottrell, Y. Bazilevs. Isogeometric analysis: CAD, finite elements, NURBS, exact geometry and mesh refinement.Computational methods applied Mechanical Engineering, vol 194, no 39- 41, pp 4135- 4195, 2005.
- [5] R.Sevilla, S.Fernández-Méndez, A.Huerta. Nurbs-Enhanced Finite Element Method. International Journal for numerical methods in engineering Vol 00; pp 1-6, 2007.
- [6] David E.Cardoze, Gary L. Miller, Mark Olah, Todd Phillips. A Bézier-Based Moving Mesh Framework for Simulation with Elastic Membranes.2004.
- [7] N. Montés, F.Sánchez, L. Hilario, A. Falcó. Flow Numerical Computation through Bézier Shape Deformation for LCM process simulation methods. International Journal of material forming, (ESAFORM) 2008. Vol. 1 pp 919-922. Lyon (France).